

MS LUBE 4T POWER

API SM, JASO MA2, SAE 20W-40

FOUR-STROKE MOTORCYCLE ENGINE OIL

DESCRIPTION

Premium performance, shear-stable, multigrade gasoline engine oil specifically designed for use in four- stroke motorcycles and portable power equipment requiring API SM JASO MA2 lubricants, including high output engines operating in severe service

APPLICATION

- Air and liquid-cooled four-stroke motorcycle engines
- Particularly suitable for Japanese high performance motorcycle engines
- Motorcycles with and without oil immersed clutches
- Motorcycles with combined engine/transmission units or separate gear boxes where a multigrade engine oil is specified
- Motorcycles with back torque limiters
- Motorcycles with exhaust catalytic converters
- Latest generation, four-stroke scooter engines
- Four-stroke gasoline engines fitted to portable power equipment, such as generators, mowers, etc

PERFORMANCE STANDARDS

- API SM
- JASO MA2

BENEFITS

- Prolongs engine life
- Saves on maintenance
- Lively throttle response
- Good all-temperature prote

KEY PROPERTIES

| SAE GRADES | 20W-40 |
|--|--------|
| Kinematic Viscosity @ 100°C (mm ² /s) | 15 |
| Kinematic Viscosity @ 40°C (mm ² /s) | 130.9 |
| Viscosity Index | 130 |
| Pour Point (°C) | -24 |
| Flash Point (°C) | 240 |
| TBN, mg KOH/g (ASTM 2896) | 7.3 |

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by MS PLUS LUBE PVT.LTD