

MS LUBE MG CAR OIL

Diesel Engine Oil
API CH-4, SAE 15W-40

AUTOMATIC MULTIGRADE ENGINE OIL

DESCRIPTION

Premium performance, multigrade, diesel engine oil specifically designed to lubricate a wide range of diesel engines requiring API CH-4 performance lubricants operating under the most severe service conditions.

APPLICATION

- Mixed fleets of diesel engines (high-speed, four-stroke, turbocharged or naturally aspirated)
- Three / Four Wheel light duty commercial vehicles
- Mixed fleets including both old and new equipment

PERFORMANCE STANDARDS

- API CH-4

BENEFITS

- **Minimizes fleet maintenance costs**
 - o Exceptional soot dispersancy keeps fuel soot in suspension, avoiding filter plugging, cylinder head sludge, abrasive polishing wear and oil thickening.
- **Minimizes fleet operating costs**
 - o Excellent deposit control on valves and piston crownlands reduces oil consumption.
 - o Exceptional oxidation stability and soot control extends oil drain capability so that equipment is in service longer generating revenue.
 - o Outstanding valve train wear protection maintains fuel economy.
- **Extends engine life to overhaul**
 - o High level of anti-wear additive protects against valve train wear and scuffing of highly loaded parts operating under boundary lubrication conditions.

KEY PROPERTIES

SAE Grade	Viscosity (mm ² /s)		Viscosity Index	Pour Point (°C)	Base Number D2896, Mg KOH/g	Flash Point (°C)
	@40°C	@100°C				
15W-40	110.5	14.91	140	-36	9.8	232

MS PLUS LUBE Private Limited |

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by MS PLUS LUBE PVT.LTD