

# MS LUBE GEAR TAG GL-5

SAE 75W-90 / 80W-90 / 85W-140

## MULTIGREAD AUTOMOTIVE GEAR OIL

### DESCRIPTION

High-performance, multipurpose, thermally stable, EP automotive gear lubricant.

### APPLICATION

- Recommended for automotive hypoid gear applications requiring lubricants meeting API Service GL-5 or where EP, multi-purpose or hypoid type gear oils are specified.
- Recommended where loading is severe and maximum gear protection is required. “Clean gear” technology makes it particularly suitable where gear oil temperatures are high.
- Not recommended for manual transmissions and transaxles where the manufacturer specifies API GL-4 (mild-EP) lubricants, or where the manufacturer advises against the use of API GL-5 (multipurpose, hypoid) lubricants.

### PERFORMANCE STANDARDS

- API GL-5

### BENEFITS

- Provides long equipment life by resisting gear wear and scuffing, Reduced maintenance cost
- Maximizes equipment availability by avoiding premature failure or need for overhaul due to deposit-induced seal wear and leakage.
- Provides long oil service life by resisting oxidation and oil thickening.
- Provides protection against corrosion of ferrous and non-ferrous components.

### KEY PROPERTIES

SAE Grades	75W-90	80W-90	85W-140
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	85.7	135.6	343.9
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	14.56	14.1	25.5
Viscosity Index	178	109	97
Pour Point (°C)	-43	-27	-15
Pour Point (°C)	225	236	248

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by MS PLUS LUBE PVT.LTD