

MS LUBE MP-3 GREASE

MULTIPURPOSE GREASE

DESCRIPTION

Multipurpose grease containing highly refined mineral base oils, lithium thickener and rust and oxidation inhibitors. Suitable for automotive and industrial applications.

APPLICATION

- Plain and rolling element bearings.
- Automotive and General plant lubrication.
- Construction equipment bearings.
- Earthmoving, quarrying and mining.
- Agricultural equipment.

Usable temperature range: -20 to +130°C. Maximum temperature for short term exposure: +155°C.

PERFORMANCE STANDARDS

- NLGI 3.

BENEFITS

- **Saves on maintenance.**
 - Protection against component wear under moderate load conditions.
 - Rust and corrosion inhibitors protect metal surfaces.
- **Long service life.**
 - Excellent oxidation resistance ensures enhanced grease service life.
- **Minimizes inventory costs.**
 - Multipurpose capability allows use in a wide range of industrial and automotive applications reducing the number of different greases required and eliminating product misapplication.

KEY PROPERTIES

NLGI Grade	3
Thickener	Lithium Soap
Penetration, Worked @ 25°C	235
Dropping Point, °C	196
Copper Corrosion @ 100°C, 24hrs	1b max
Oxidation Stability, kgf/cm ² @ 99°C, 100hrs	0.4